

## Product information:

---

The CAV118 is an adapter cable from SVGA male to 5x BNC male for connecting an SVGA signal to a BNC monitor. The SVGA connector is gold plated, for an optimal connection and signal quality. The BNC connectors are colored differently and serving for red, green, blue, horizontal and vertical synchronization.

## Components:


---

- CableType: SGVA101 - Video Cable



## Properties:

---



## Product Features:

---

Application

AV & IT

## Physical Characteristics:

---

Type of cable	75 Ω VGA video cable		
Filling	PP		
Inner conductor	American Wire Gauge	28 AWG	
	Insulation	Material	FPE 1.7 mm (Ø)
		Colours	White
	Shielding	Spiral	BC 54 x 0.12 mm (Ø) (OFC)
Inner jacket	Material	Temperature resistant PVC (105°C)	
	Colours	Black / White / Red / Green / Blue	
Overall shielding	Aluminium foil	Al-mylar, 100% coverage - 25% Overlap	
	Braiding	TC 16 x 7 x 0.12 mm (Ø) (OFC)	
Outer jacket	Material	PVC 11 mm (Ø)	
	Colours	Black	
Inner conductor	Material	BC 54 x 0.12 mm (Ø) (OFC)	
Fitted connectors	BNC male		
	SVGA male		

## Variants:

---

- CAV118/1.5-H - 1.5 meter - hanger
- CAV118/3-H - 3 meter - hanger
- CAV118/5-H - 5 meter - hanger
- CAV118/10-H - 10 meter - hanger
- CAV118/15-H - 15 meter - hanger
- CAV118/20-H - 20 meter - hanger

## Component details:

---

# SGVA101

## Video Cable

This cable is a cable only used as a production component for PROCAB pre-made cables and is not sold separately or in bulk. Consult the productsheet for detailed information.