

Highlights:

- 28 AWG thin and dense stranded conductors
- Flexible PVC jacket
- Spiral shielding
- Oxygen free copper
- 4 x 8 mm (Ø) outer diameter

Product information:

The CAB800 is fitted with two RCA male connectors on both sides and is constructed using the SIG44 cable. The easy to handle PVC jacket is excellent for fixed indoor and mobile applications. The inner conductors are fitted with a durable shielding. This gives an excellent protection against interference of all kinds such as electromagnetic fields produced by dimmers, electric motors or power cables. The SIG series cables are “all-round” signal cables which are suited for all kinds of applications where reliable signal transmission is needed. It comes in lengths of 0.5 meters up to 20 meters, providing solutions for all applications.



Components:

- CableType: SIG44 - Signal Cable

Properties:




Product Features:

Application	AV & IT
Series	Classic Series

Physical Characteristics:

Inner conductor	Insulation	Material	PE 1 mm (Ø)
		Colours	White / Red
		Shielding	CCA 8 x 4 mm (Ø)
Outer jacket	Material	PVC 8 x 4 mm (Ø)	
		Colours	Black
Type of cable		28 AWG Stereo signal cable	
Inner conductor	Material	BC 7 x 0.12 mm (Ø) (OFC)	
		Section	0.00013 "²
		Number of conductors	2

Wiring Diagrams:



Variants:

- CLA800/0.5 - 0,5 meter
- CLA800/1 - 1 meter
- CLA800/1.5 - 1,5 meter
- CLA800/3 - 3 meter
- CLA800/5 - 5 meter
- CLA800/10 - 10 meter
- CLA800/15 - 15 meter
- CLA800/20 - 20 meter

Component details:

SIG44
Signal Cable

This cable is a cable only used as a productioncomponent for PROCAB pre-made cables and is not sold seperately or in bulk. Consult the productsheet for detailed information.