

Highlights:


- 18 AWG thin and dense stranded conductors
- Flamoflex™ IEC 60332-1 installation jacket
- IEC 60332-1 NHFR compliant

Product information:

The CLS2xx series are 2-core installation loudspeaker cables featuring a Flamoflex™ outer jacket compliant to the IEC 60332-1 standard regarding fire and flammability resistance in public installations. The Flamoflex™ material is specifically designed with installers convenience in mind, offering a smooth and durable outer jacket for easy installation and pulling. This series consists of 4 models with individually NHFR isolated conductors in sections from 0.75 mm² (18 AWG) up to 4.0 mm² (11 AWG) which are composed of stranded tinned copper wires. The stranding keeps the cable flexible and easy to handle, while the tinned copper conductor material significantly improves the corrosion and oxidation resistance of the cable, enabling it to be used indoors as well as outside, in humid or marine environments.



Properties:



Inner Conductors:



Product Features:

Application	AV & IT
Series	Contractor Series

Physical Characteristics:

Inner conductor	Insulation	Material	NHFR 1.9 mm (Ø)	
			NHFR 1.9 mm (Ø)	
			Colours	Red / Blue
Outer jacket	Material			NHFR 5.8 mm (Ø)
		Colours	Black	
Type of cable				2-core loudspeaker cable
Inner conductor	Material	TC 24 x 0.2 mm (Ø) (OFC)		
		Section	0.0012 "²	
Filling				NHFR
Separator				None
Inner conductor	American Wire Gauge	18 AWG		
		Number of conductors	2	
		Conductor twisting	Yes	

Standards & regulations:

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006
Flammability test	According IEC 60332-1
Indoor / outdoor	UV resistant (UL1581, UVA, 720 h)
Circuit integrity	n/a
Smoke emissions	According IEC 61034
Zero halogen compounds	According EN 50267-2-1
	IEC 60754

Electrical Characteristics:

Max. conductor	DC resistance	29.1 (Ω / Km)
Dielectric strength	2 (KV / 1 min. DC)	
Rated voltage	300 V	

Mechanical Characteristics:

Temperature range	Fixed installation	- 68 °F till + 176 °F
	Mobile installation	- 59 °F till + 140 °F
Bending radius	Fixed installation	8 x outer diameter
	Mobile installation	10 x outer diameter

Cross sections:

---

