

### Highlights:

---

- Integrated stereo audio section
- Flexible PVC jacket
- 28 AWG thin and dense stranded conductors
- 0.30 " (Ø) outer diameter
- Oxygen free copper
- Double Al-foil shielding

### Product information:

---

CLV115 is a high quality SVGA cable with 5 coaxial conductors carrying the RGBHV signals. A aluminium foil shielding will grant with 100% coverage. EDID and DDC are supported. The connectors are gold plated to ensure maximum connectivity. All pins are connected. On one side, the mini jack cable end is 15 cm (projector side) and on the other side (computer side) the mini jack cable end is 50 cm.



### Components:

---

- CableType: SVGA215 - Audio + Video Cable

### Properties:

---



### Product Features:

---

Application	AV & IT
Series	Classic Series

## Physical Characteristics:

---

Inner conductor	Insulation	Material	FPE 1.55 mm (Ø)		
		Colours	White		
	Shielding	Aluminium foil	Al-mylar, 100% coverage - 25% Overlap		
		Drain wire	BC 7 x 0.12 mm (Ø) (OFC)		
	Audio	Insulation	Material	PE 7540 0.7 mm (Ø)	
			Colours	Grey / Purple	
		Shielding	Spiral	CCA 28 x 0.12 mm (Ø)	
Overall shielding	Aluminium foil			Al-mylar, 100% coverage - 25% Overlap	
		Drain wire		BC 7 x 0.16 mm (Ø) (OFC)	
Outer jacket	Material			PVC 7.5 mm (Ø)	
				Colours	Black
Type of cable					75 Ω VGA video cable
Inner conductor	Material				BC 7 x 0.12 mm (Ø) (OFC)
	Audio	Material			BC 10 x 0.12 mm (Ø) (OFC)
Filling					Cotton Yarn
Inner conductor	American Wire Gauge				28 AWG
Fitted connectors					SVGA male

## Variants:

---

- CLV115/15 - 15 meter
- CLV115/20 - 20 meter
- CLV115/25 - 25 meter
- CLV115/30 - 30 meter

## Component details:

---

# SVGA215

## Audio + Video Cable

This cable is a cable only used as a production component for PROCAB pre-made cables and is not sold separately or in bulk. Consult the productsheet for detailed information.