


### Highlights:

- Made in EU
- All-in-one solution
- Custom installation
- Easy and fast installation
- Combine multiple cables cores in one single cable

### Product information:

The PAC151 is a hybrid power/audio cable which can be used in a variety of applications. The cable consists of 3 x 1,5mm<sup>2</sup> power section and a 2 x 0.22mm<sup>2</sup> 110 Ohm signal pair. The signal pair can be used for analog audio, digital audio or DMX. The power and signal cable each have a separate jacket which makes it easy to split out the cables at the end.




### Components:

- CableType: HMX224 - 24 AWG Balanced signal / DMX-AES cable
- CableType: HPC3G1.5 - 3G1.5 3 x 1.5 mm<sup>2</sup> PVC power cable

### Certification:



### Properties:



### Product Features:

Application	Rental & MI
Series	Bulk & Accessories

## Physical Characteristics:

---

Components		1 x HMX224
		1 x HPC3G1.5
Outer jacket	Material	Highflex PVC 15.9 mm (Ø)
	Colours	Black
Type of cable		Power & 1 x DMX-AES 110 Ω cable
Filling		Non-woven (PET/PA) tape

## Standards & regulations:

---

RoHS2 compliant	According EU Directive 2011/65/EU
Reach compliant	According EC 1907/2006
Flammability test	According EN 60332-1-2

## Mechanical Characteristics:

---

Temperature range	Fixed installation	- 15 °C till + 70 °C
	Mobile installation	- 5 °C till + 75 °C
Bending radius	Fixed installation	6 x outer diameter
	Mobile installation	8 x outer diameter


## Variants:

---

- PAC151/1 - 100 meter
- PAC151/3 - 300 meter

## Cross sections:

---




## Component details:

# HMX224

## 24 AWG Balanced signal / DMX-AES cable

This cable is only used as a production component for PROCAB pre-made cables and is not sold separately or in bulk. Consult the product sheet for detailed information about this component.



### Physical Characteristics:

Inner conductor	Audio	Material	TC 7 x 0.2 mm (Ø) (OFC)	
		Section	0.00034 <sup>42</sup>	
		American Wire Gauge	24 AWG	
		Number of conductors	2	
		Insulation	Material	PE 1.5 mm (Ø)
			Colours	Red / Blue
		Shielding	Aluminium foil	Al-mylar, 100% coverage - 25% Overlap
			Drain wire	TC 7 x 0.2 mm (Ø) (OFC)
			Braiding	TC 7 x 16 x 0.1 mm (Ø) (OFC)
Filling				Non-woven (PET/PA) tape
Outer jacket	Material			PVC 5.0 mm (Ø)
	Colours			Black

## Electrical Characteristics:

Max. conductor	DC resistance	85 ( $\Omega$ / Km)
Max. shielding	DC resistance	25 ( $\Omega$ / Km)
Audio		47 (pF/m)
Characteristic impedance		110 $\Omega \pm 10\% \Omega$
Nom. Velocity of propagation		75 %
Return loss (dB)		(From 1 to 25 mHz) > 20 dB
Dielectric strength		(Cond/Shield) 1.2 (KV / 1 min. DC)
		(Cond/Cond) 0.5 (KV / 1 min. DC)

# HPC3G1.5

## 3G1.5 3 x 1.5 mm<sup>2</sup> PVC power cable

This cable is only used as a production component for PROCAB pre-made cables and is not sold separately or in bulk. Consult the product sheet for detailed information about this component.



## Physical Characteristics:

Inner conductor	Power	Material	BC 28 x 0.25 mm ( $\emptyset$ ) (OFC)
		Section	0.0023 <sup>42</sup>
		American Wire Gauge	16 AWG
		Number of conductors	3
		Insulation	Material PVC 3 mm ( $\emptyset$ )
		Colours	Blue / Brown / Yellow & Green
Outer jacket	Colours		Black
	Material		PVC 8.3 mm ( $\emptyset$ )

## Electrical Characteristics:

---

Max. conductor	DC resistance	13.3 ( $\Omega$ / Km)
Resistance	Insulation	> 200 M $\Omega$ / km
Rated voltage		U <sub>0</sub> /U 300/500 V
Dielectric strength		2.5 (KV / 1 min. DC)