

Highlights:

- Ultraflex™ Ultra flexible jacket
- Oxygen free copper
- 60 mm transparent shrink sleeve
- Black sleeve to prevent separation (removable)
- Silver contacts, black metal XLR housing
- Gold contacts, scratch resistant black shell
- Zinc diecast shell (Black Cr plated)

Product information:

These PROCAB prime series cables are designed for high demanding professional applications where High connectivity and durability are desired, so that even after years of use in the hardest environments these cables will still excel in their reliability.

Composed using the PSG124 UltraFlex™ cable this cable is guaranteed to remain straight and flat no matter how it's treated, making it ideal for on stage use. The PVC outer jacket provides a flexible but solid feel while making it able to withstand an extreme amount of bending cycles.

The male PROCAB PRIME RCA connector (PCR2M) ensures high connectivity thanks to its durable gold contacts. This, in combination with its scratch resistant black shell makes this connector excellent for high demanding professional use. Both connectors are provided with a red or white colored ring to easily define the audio channel.

The male XLR connector (NC3MXX-BAG) from Neutrik is the worldwide accepted standard for XLR connectors, manufactured with a black chrome plated Zinc diecast shell housing durable silver contacts providing the highest possible contact integrity for many years to come. The perfected chuck type strain relief provides higher pull out force while offering fast and easy assembling.

Components:

- Connector: PCR2M - Cable connector - professional RCA/Cinch male - gold contacts - pair

Product Features:

Application	Rental & MI
Series	Prime Series



Certification:



Properties:



Wiring Diagrams:

Variants:

- PRA701/3 - 3 meter

