PROMO6A-CLS240-CCA

Sample pack CLS240-Cca

Highlights:

- 11 AWG (4 mm²) thin and dense stranded conductors
- Class 5 IEC 60228 compliant
- EN50399 CPR Euroclass Cca-s1,d0,a1

Product information:

1 meter sample pack of the CLS240-Cca. The CLS240-Cca series are 2-core installation loudspeaker cables compliant to the Cca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.

In addition to its outstanding fire properties the outer jacket of the cabling is smooth and durable for easy installation and pulling. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.

More information about CPR compliant cables? Click here



Certification:

CCA
CPR

Properties:

Meter indicator

LSHF

Inner Conductors:

STRANDED OXYGEN FREE
COPPER

Product Features:

Application	AV & IT
	Rental & MI
Series	Bulk & Accessories

We reserve the right to change specifications without notice, this is part of our policy to continually improve our products.


Physical Characteristics:

Type of cable			2-core loudspeaker cable
EN50399 CPR Euroclass			Cca-s1b,d0,a1
Inner conductor	Material		BC 48 x 0.31 mm (Ø) (OFC)
	Section		0.0062 “²
	Number of conductors		2
	Insulation	Material	Polyolefin 4 mm (Ø)
Filling			None
Separator			None
Inner conductor	American Wire Gauge		11 AWG
	Insulation	Colours	Red / Blue
	Conductor twisting		Yes
Outer jacket	Material		Polyolefin 10.2 mm (Ø)
	Colours		Black

Electrical Characteristics:

Max. conductor	DC resistance	4.95 (Ω / Km)
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

Cross sections:



We reserve the right to change specifications without notice, this is part of our policy to continually improve our products.