

## Highlights:

---

- 14 AWG (2.5 mm<sup>2</sup>) thin and dense stranded conductors
- EN50399 CPR Euroclass B2ca-s1a,d0,a1
- Compact & tight jacket
- Reduced outer diameter for optimized cable tray usage
- Double isolated
- Smooth & durable outer jacket
- Oxygen free copper conductors
- Meters indication marking

## Product information:

---

1 meter sample pack of the CLS425C-B2CA.

The CLS425-B2ca series are 4-core installation loudspeaker cables compliant to the B2ca standards of the Construction Product Regulation (CPR) regarding fire and flammability resistance in fixed installations, minimizing toxic smokes and providing optimal resistance to spreading fire.


In addition to its outstanding fire properties, the outer jacket of the cabling is smooth and durable for easy installation and pulling. The stranding keeps the cable flexible and easy to handle. The cable can be used in both indoor and outdoor or in humid environments.

More information about CPR compliant cables? [Click here](#)




## Certification:

---



## Properties:

---



## Inner Conductors:

---



## Product Features:

Application	AV & IT
Series	Contractor Series

## Physical Characteristics:

Type of cable	4-core loudspeaker cable	
EN50399 CPR Euroclass	B2ca-s1a,d0,a1	
Inner conductor	Section	0.0039 "2
	Number of conductors	4
	American Wire Gauge	14 AWG
	Material	BC 50 x 0.25 mm (Ø) (OFC)
Insulation	Material	LSZH 2.7 mm (Ø)
	Colours	Black / Red / Blue / Yellow
	Conductor twisting	Yes
Outer jacket	Material	LSZH 8.0 mm (Ø)
	Colours	Black

## Standards & regulations:

Reach compliant	According EC 1907/2006
RoHS2 compliant	According EU Directive 2011/65/EU
CPR Euroclass	B2ca-s1a,d0,a1
Flammability test	According EN 60332-1-2
Indoor / outdoor	UV resistant (UL1581, UVA, 720 h)
Smoke emissions	According IEC 61034
Zero halogen compounds	According EN 50267-2-1
	IEC 60754

## Electrical Characteristics:

Max. conductor	DC resistance	0.798 Ω / 100 m
Dielectric strength		2000 V/min
Rated voltage		300 V

## Mechanical Characteristics:

Temperature range	Fixed installation	- 20 °C till + 80 °C
Bending radius	Fixed installation	> 7.5 x outer diameter
UV resistant		Yes