



Product information:

1 meter sample pack of the PAC252. The PAC252 is a hybrid power/audio cable which consists of 3 x 2,5mm² power section and two times a 2 x 0.22mm² 110 Ohm signal pair. The dual signal pair makes it ideal for applications where a stereo signal is needed or where the second pair is used as redundancy. The power and the 2 signal cables each have a separate jacket which makes it easy to split out the cables at the end.




Certification:



Properties:





Product Features:

Application	AV & IT
	Rental & MI
Series	Bulk & Accessories

PROCAB - PROMO6H-PAC252 - 02/12/2025 03:21 UTC

Physical Characteristics:

Outer jacket	Material			PVC 18 mm (Ø)
	Colours			Black
Inner conductor	Audio	Insulation	Material	PE 1.55 mm (Ø)
Inner jacket	Material			PVC 5 mm (Ø)
				PVC 10 mm (Ø)
Inner conductor	Power	Insulation	Material	PVC 3.7 mm (Ø)
	Audio	Insulation	Colours	Red / Blue
		Shielding	Drain wire	TC 7 x 0.2 mm (Ø) (OFC)
	Power	Insulation	Colours	Blue / Brown / Yellow & Green
Type of cable				Power & 2 x DMX-AES 110 Ω cable
Inner conductor	Power	Material		BC 48 x 0.25 mm (Ø) (OFC)
		Section		0.0039 "2
	Audio	Material		TC 7 x 0.2 mm (Ø) (OFC)
		Section		0.00034 "2
	Power	American Wire Gauge		13 AWG
	Audio	American Wire Gauge		24 AWG
	Power	Number of conductors		3
	Audio	Number of conductors		2

Electrical Characteristics:

Max. conductor	DC resistance	85 (Ω / Km)
		7.98 (Ω / Km)
Max. operation voltage	Power	500 V
Characteristic impedance		110 Ω ± Ω

Cross sections:

