

PROMO6H-PNC2517 Sample pack PNC2517

Product information:

1 meter sample pack of the PNC2517. The PNC2517 is a hybrid power/network cable which consists of 3 x 2,5mm² power section and a CAT 7 LAN cable. As more and more audio/video/light equipment is network-based this cable is perfectly suited to provide the necessary power and data to these devices. The power and LAN cable each have a separate jacket which makes it easy to split out the cables at the end.



Certification:



Properties:



Product Features:

| Application | AV & IT |
|-------------|--------------------|
| | Rental & MI |
| Series | Bulk & Accessories |

PROCAB - PROMO6H-PNC2517 - 26/04/2024 00:01 UTC

Physical Characteristics:

| Outer jacket | Material | | | PVC 20.3 mm (Ø) |
|-----------------|----------|---------------------|----------|---|
| | Colours | | | Black |
| Inner jacket | Material | | | PVC 10 mm (Ø) |
| | | | | PVC 6.3 mm (Ø) |
| Inner conductor | Power | Insulation | Material | PVC 3.7 mm (Ø) |
| | Data | Insulation | Material | FPE 1.55 mm (Ø) |
| | | | Colours | Green / White & Green ; Blue / White & Blue ; Orange / White & Orange ; Brown / White & Brown |
| | Power | Insulation | Colours | Blue / Brown / Yellow & Green |
| | Data | Material | | BC 1 x 0.13 mm (Ø) (OFC) |
| | Power | Material | | BC 48 x 0.25 mm (Ø) (OFC) |
| | Data | Section | | 0.00020 "2 |
| | Power | Section | | 0.0039 "2 |
| | Data | American Wire Gauge | | 26 AWG |
| | Power | American Wire Gauge | | 13 AWG |
| | | Number of conductor | 5 | 3 |
| | Data | Number of conductor | 5 | 8 (4 pairs) |

Electrical Characteristics:

Cross sections:

| Max. conductor | DC resistance | 148 (Ω / Km) |
|------------------------|---------------|---------------|
| | | 7.98 (Ω / Km) |
| Max. operation voltage | Power | 500 V |

