

Highlights:



- Parallel & separable wires
- 3 x coaxial (RGB)
- 24 AWG stranded coaxial
- Double shielding (Al-foil + Spiral)

Product information:

The RGB600 is a high quality RGB-video cable for all high resolution RGB-video interconnects. It contains 3 shielded coax cables, all with solid Oxygen free copper conductors, foamed polyethylene dielectric and braided shielding. The coax cables feature a high velocity of propagation and minimal return loss to ensure quality signal delivery on longer connections. Compatible with Neutrik BNC connector NBNC75BFH6.



Properties:



Inner Conductors:



Shielding:



Product Features:

Application	AV & IT
Series	Bulk & Accessories

Physical Characteristics:

Inner conductor	Insulation	Material	FPE 3.2 mm (Ø)
		Colours	Red / Green / Blue
Outer jacket	Material		Flexible PVC 3 x 6 mm (Ø)
	Colours		Black
Type of cable			75 Ω coaxial video cable
Inner conductor	Material		BC 20 x 0.12 mm (Ø) (OFC)
	Section		0.00034 "²
	American Wire Gauge		24 AWG
	Number of conductors		3

Mechanical Characteristics:

Temperature range	Fixed installation	- 40 °C till + 80 °C
	Mobile installation	- 15 °C till + 60 °C
Bending radius	Fixed installation	6 x outer diameter
	Mobile installation	8 x outer diameter

Cross sections:

