

Highlights:

- Parallel & separable wires
- 16 AWG thin and dense stranded conductors
- Color coded polarity identification

Product information:

The RZ series cables are parallel designed loudspeaker cables with a maximum flexibility and strength. They are mostly used for indoor applications. Each conductor is fitted with a highly flexible PVC jacket. The two parallel conductors are in black colour and one of the two has a thin red line to identify the polarity. The RZ series cables are “all-round” loudspeaker cables suited for all kinds of applications on loudspeaker level.



Inner Conductors:



Product Features:

Application	AV & IT
Series	Bulk & Accessories

Physical Characteristics:

Type of cable	2-core loudspeaker cable	
Inner conductor	Material	BC 20 x 7 x 0.12 mm (Ø) (OFC)
	Section	0.0023 ⁴²
	Number of conductors	2
	American Wire Gauge	16 AWG
Outer jacket	Material	Flexible PVC 3 x 6 mm (Ø)
	Colours	Black with red molded line

Mechanical Characteristics:

Temperature range	Fixed installation	- 40 °C till + 80 °C
-------------------	--------------------	----------------------

	Mobile installation	- 25 °C till + 70 °C
--	---------------------	----------------------

Bending radius	Fixed installation	8 x outer diameter
----------------	--------------------	--------------------

	Mobile installation	10 x outer diameter
--	---------------------	---------------------


Electrical Characteristics:

Capacitance	Cond/Cond	95 pF / m @ 1 kHz
-------------	-----------	-------------------

Lead resistance		1.2 Ω / 100 m
-----------------	--	---------------

Cable Crosstalk		Min. 74 dB / 100 m
-----------------	--	--------------------

Cross sections:



Variants:

- RZ15/1 - 100 meter