

Highlights:

- Parallel & separable wires
- 13 AWG thin and dense stranded conductors
- Color coded polarity identification

Product information:

The RZ series cables are parallel designed loudspeaker cables with a maximum flexibility and strength. They are mostly used for indoor applications. Each conductor is fitted with a highly flexible PVC jacket. The two parallel conductors are in black colour and one of the two has a thin red line to identify the polarity. The RZ series cables are “all-round” loudspeaker cables suited for all kinds of applications on loudspeaker level.



Inner Conductors:



Product Features:

| | |
|-------------|--------------------|
| Application | AV & IT |
| Series | Bulk & Accessories |

Physical Characteristics:

| | | |
|-----------------|--------------------------|-------------------------------|
| Type of cable | 2-core loudspeaker cable | |
| Inner conductor | Material | BC 30 x 7 x 0.12 mm (Ø) (OFC) |
| | Section | 0.0039 ⁴² |
| | Number of conductors | 2 |
| | American Wire Gauge | 13 AWG |
| Outer jacket | Material | Flexible PVC 4 x 8 mm (Ø) |
| | Colours | Black with red molded line |

Mechanical Characteristics:

| | | |
|-------------------|--------------------|----------------------|
| Temperature range | Fixed installation | - 40 °C till + 80 °C |
|-------------------|--------------------|----------------------|

| | | |
|--|---------------------|----------------------|
| | Mobile installation | - 25 °C till + 70 °C |
|--|---------------------|----------------------|

| | | |
|----------------|--------------------|--------------------|
| Bending radius | Fixed installation | 8 x outer diameter |
|----------------|--------------------|--------------------|

| | | |
|--|---------------------|---------------------|
| | Mobile installation | 10 x outer diameter |
|--|---------------------|---------------------|

Electrical Characteristics:

| | | |
|-------------|-----------|--------------------|
| Capacitance | Cond/Cond | 118 pF / m @ 1 kHz |
|-------------|-----------|--------------------|

| | | |
|-----------------|--|---------------|
| Lead resistance | | 0.9 Ω / 100 m |
|-----------------|--|---------------|

| | | |
|-----------------|--|--------------------|
| Cable Crosstalk | | Min. 74 dB / 100 m |
|-----------------|--|--------------------|

Cross sections:

